

## Amendments to the Claims

This listing of claims will replace all prior versions and listings of claims in the application:

### Listing of Claims:

1. (Currently Amended) A method for generating a message integrity code in a wireless local area network operating under an IEEE 802.11 standard, comprising:

separate a message into a plurality of fragments;

suppressing a sequence number input to a message integrity code (MIC)

algorithm[[]]; ~~and~~

calculating a message integrity code based in part on a fragment number;

encrypting the MIC without the sequence number;

assigning packet numbers to message fragments in the order of fragmentation;

assigning a sequence number to the message which is the same for each

message fragments; and

transmitting the message to a receiving station by a transmitter.

- 2 - 4. (Cancelled).

5. (Currently Amended) A method according to Claim 4<sub>1</sub>, further comprising, upon receipt of a plurality of messages having the same sequence number at a receiving station, checking the received packet numbers for a complete sequence.

6. (Original) A method according to Claim 5, further comprising rejecting a message if it does not have a complete sequence of packet numbers.

7. (Currently Amended) In a wireless local area network message protocol in which each data unit is assigned a sequence number and a fragment number, a method of generating a message integrity code (MIC) for a data unit comprising;

using the fragment number, but not the sequence control number as an input to a message integrity code (MIC) algorithm; and  
generating the MIC before the sequence number has been assigned to a packet;

8 - 9 (Cancelled).

10. (Currently Amended) The method of Claim 7, further comprising assigning a packet number to each message fragment, receiving messages at a receiving station and checking packet numbers of received message for a complete sequence of packet numbers.

11. (Original) The method of Claim 10, further comprising rejecting messages which do not have a complete sequence of packet numbers.

12. (Currently Amended) A method for providing security for messages transmitted over a wireless local area network, wherein the messages have a transmitted message integrity code (MIC) encrypted without a sequence number and assigned packet numbers to message fragments in the order of fragmentation, said method comprising:

receiving, by a receiver, a plurality of messages with the same sequence number;

and

checking the packet numbers of each of the plurality of messages in the order received to determine whether the plurality of messages include a complete sequence of packet numbers

~~assigning sequence numbers to all messages in the order of transmission and~~

~~including the sequence number in each transmitted message,~~

~~assigning fragment numbers to all messages in the order of fragmentation of~~

~~each message and including the fragment number in each transmitted message, and~~

~~calculating a transmitted message integrity code based in part on the fragment~~

~~number for each transmitted message and including the transmitted message integrity code in each transmitted message.~~

13. (Cancelled).

14. (Original) A method according to Claim 12, further comprising:

upon receipt of a message, calculating a received message integrity code based in part on the fragment number for the received message.

15. (Original) A method according to Claim 14, further comprising:  
comparing the transmitted message integrity code to the received message integrity code.
16. (Original) A method according to Claim 15, further comprising:  
rejecting the received message if the transmitted message integrity code does not match the received message integrity code.
17. (Cancelled).
18. (Original) A method according to Claim ~~47~~12, further comprising:  
if the plurality of messages has an incomplete sequence of packet numbers,  
rejecting the messages identified by the sequence number.
19. (Currently Amended) A wireless network station comprising a processor programmed to:  
suppress a sequence number input to a message integrity code (MIC)  
algorithm[[]]; and  
calculate a message integrity code based in part on a fragment number.  
encrypt the MIC without the sequence number;  
assign a packet number to each message fragment in the order of fragmentation;  
and

assign a sequence number to the message which is the same for each message fragments.

20. (Original) A wireless network station according to Claim 19 wherein the processor is programmed to:

transmit a message including the message integrity code over a wireless local area network.

21. (Currently Amended) A wireless network station according to Claim 19 wherein the processor is programmed to:

receive a message including a message integrity code over a wireless local area network[[,]]; and

suppress a sequence number input to a message integrity code algorithm[[,]]; and

calculate a message integrity code for the received message based in part on a fragment number.

22. (Currently Amended) A wireless network station according to Claim 21 wherein the processor is programmed to:

compare the message integrity code of the received message to the message integrity code calculated for the received message[[,]]; and

if the message integrity code of the received message does not match the message integrity code calculated for the received message, reject the received message.

23. (Currently Amended) A wireless network station according to Claim 21 wherein the processor is programmed to:

upon receipt of a plurality of messages having a common sequence number,  
check packet numbers of the messages for a complete sequence[.]; and  
if the packet number sequence is not complete, reject all of the received with the  
common sequence number.

24. (Currently Amended) A wireless network station comprising a processor programmed to:

assign sequence numbers to all messages in the order of transmission and  
include the sequence number in each transmitted message[.];  
assign fragment numbers to all messages in the order of fragmentation of each  
message and include the fragment number in each transmitted  
message[.]; and  
calculate a transmitted message integrity code based in part on the fragment  
number for each transmitted message and include the transmitted  
message integrity code in each transmitted message.

25. (Currently Amended) A wireless network station according to Claim 24 wherein the processor is programmed to:

upon receipt of a message, calculate a received message integrity code based in part on the fragment number for the received message[[,]]; and

compare the transmitted message integrity code to the received message integrity code[[,]]; and

reject the received message if the transmitted message integrity code does not match the received message integrity code.

26. (Currently Amended) A wireless network station according to Claim 24 wherein the processor is programmed to:

upon receiving a plurality of messages having the same sequence number, check the packet numbers of each of the plurality of messages to determine whether the plurality of messages include a complete sequence of packet numbers[[,]]; and

if the plurality of messages has an incomplete sequence of packet numbers, reject the messages identified by the sequence number.